

Pneumatic Slurry Pump



Double Diaphragm Slurry pump designed for Shaft Sinking, Drives, decline, Ramps, Tunnels & Dams with the Head delivery of 40 – 70 Mtrs. available in two different models – KPD-250 & KPD-170

Technical Details

	Model KPD-250	Model KPD-170
Weight	60 Kgs	25 Kgs
Dimensions	20" X 17" X 34"	17" X 12" X 24"
Discharge	250-400 LPM / 15000-24000 LPH	150-250 LPM / 9000-15000 LPH
Head Capacity	50 METER VERTICAL	35-40 METER VERTICAL
Air Consumption	90-100 CFM	70-80 CFM
Air Pressure	6-7 KG/CM2 80/90 PSI	5-6 KG CM2 70/90 PSI
Suction Size	3"(75 MM)	2"(50 MM)
Delivery Size	2" (50 MM)	2"(50 MM)
Suction Lift	10 FEET	10 FEET
Stroke Capacity	90-100 PER MINUTE	60-80 PER MINUTE
Max. Size of Solid	3/8"(10 MM)	5/16" (8 MM)
Lubricant	SERVONEUM 100	SERVONEUM 100
Self Priming	YES	YES
Submersible	YES	YES
Material of Construction	ALLUMINIUM ALLOY CASTING	ALLUMINIUM ALLOY CASTING